

BLANK PAGE



REAFFIRMED 2008

Indian Standard

PLYWOOD TEA-CHESTS-SPECIFICATION

PART 4 METAL FITTINGS

(Fifth Revision)

भारतीय मानक

प्लाईबुड चाय पेटियां - विशिष्टि माग 4 षातु क किटिंगें (पांचवां पुनरीक्षण)

UDC 621.798.123 [674-419.32:663.95]:621.88

6 BIS 1990

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

May 1990 Price Group 1

AMENDMENT NO. 1 AUGUST 1991 TO

IS 10 (Part 4): 1989 PLYWOOD TEA-CHESTS — SPECIFICATION

PART 4 METAL FITTINGS

(Fisth Revision)

(Page 1, clause 4.1, line 1) — Delete the word 'nominal'.

(Page 2, Table 2, col 3) — Insert '2' against lot size of '3 001 to 10 000'.

(Page 2, clause A-3.1, line 3) — Insert the word 'failing' after the word 'fitting'.

(CED 33)

Reprography Unit, BIS, New Delhi, India

FOREWORD

This Indian Standard (Part 4) (Fifth Revision) was adopted by the Bureau of Indian Standards on 21 December 1989, after the draft finalized by the Timber Stores Sectional Committee had been approved by the Civil Engineering Division Council.

This standard, covering provisions relating to metal fittings of plywood tea-chest, in its fourth revision (1976) was published as one of the following five parts:

- Part l General
- Part 2 Plywood
- Part 3 Battens
- Part 4 Metal fittings
- Part 5 Assembly and packing

This fifth revision of Part 4 prescribes 'waste-waste quality' tinplate or terne plate as material for metal fittings. Only the minimum thickness of metal fittings has been specified instead of giving the range of thickness. Since the testing of dimensions of metal fittings is done on a set of 12 pieces, the definition of lot size has been modified accordingly.

In the formulation of this standard due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

PLYWOOD TEA-CHESTS—SPECIFICATION

PART 4 METAL FITTINGS

(Fifth Revision)

1 SCOPE

1.1 This standard (Part 4) covers dimensions and other requirements of metal fittings used in the assembly of plywood tea-chests.

2 REFERENCES

2.1 The Indian Standard IS 4905: 1968 'Methods for random sampling' is a necessary adjunct to this standard.

3 MATERIAL

3.1 The metal fittings shall be manufactured from waste-waste quality tinplate or terne plate. The tinplate or terne plate shall have a clean smooth flat surface and shall be free from rust and serrated edges.

4 DIMENSIONS AND TOLERANCES

4.1 Thickness

The minimum nominal thickness of metal fittings for corner, top and bottom shall be 0.22 mm.

4.2 Width

The width of metal fittings for corner, top and bottom shall be $38 + \frac{3}{0}$ mm.

4.3 Length

4.3.1 The length of 4 corners and 8 pieces for top and bottom for square and rectangular teachests of the sizes mentioned shall be as given in Table 1.

4.3.2 The 4 corner pieces shall be flat with beaded edges.

4.3.3 The 8 top and bottom pieces shall be with beaded edges, angled 90° and a 'V' notch in the centre; notch extending up to the fold. The position of notch shall be as indicated in Table 1.

4.3.4 For tea-chest of size 380 mm × 685 mm × 845 mm, used exclusively for packing instant tea, the length of fittings shall be as follows:

a) For corners

4 pieces flat with beaded edges and of length 844 mm.

b) For top and bottom

- 1) 4 pieces flat with beaded edges 686 mm.
- 2) 4 pieces flat with beaded edges of length 380 mm.

NOTE - Metal fittings with straight end shall be permitted for this size only.

5 SAMPLING

5.1 The method of drawing representative samples of tea-chest fittings shall be as prescribed in Annex A.

6 MARKING

6.1 Each fitting shall be marked with indication of the source of manufacture.

Table 1 Length of Metal Fittings (Clauses 4.3.1 and 4.3.3)

81	Size of	Length		Position of
No.	Tea-Chest	Corners (4 pcs)	Top and Bottom (8 pcs)	V Notch
(1)	(2)	(3)	(4)	(5)
	mm	mm	mm	
i)	$480 \times 480 \times 600$	580	49 5	Middle
ii)	$480 \times 480 \times 560$	540	495	Middle
iii)	$460 \times 460 \times 500$	480	4 75	Middle
iv)	400 × 40 0 × 600	580	415	Middle
v)	$400 \times 400 \times 500$	48 0	4 15	Middle
vi)	$400\times400\times450$	430	415	Middle
vii)	400 × 500 × 600	580	465 × 4	At 207°5 mm from one end
			465 × 4	At 257.5 mm from one end
	Tolerances	± 3 mm	±3 mm	

ANNEX A

(Clause 5.1)

SAMPLING OF PLYWOOD TEA-CHEST FITTINGS

A-1 SAMPLING

A-1.1 Lot

In a consignment all the sets of metal fittings (4 corners and 8 top and bottom pieces) for each size of tea-chest manufactured from the same material shall be grouped together to constitute a lot.

A-1.2 Each lot shall be tested separately for determining its conformity to the requirements of the standard.

A-2 SCALE OF SAMPLING

A-2.1 The number of fittings to be selected in the sample from a lot shall depend upon the size of the lot and shall be in accordance with col 1 and 2 of Table 2.

A-2.2 The fittings for the samples shall be selected at random from the lot. For random selection of the fittings guidance may be obtained from IS 4905: 1968.

Table 2 Scale of Sampling and Criteria for Conformity

(Clauses A-2.1 and A-3.2)

Lot Size	Sample Size	Permissible No. of Defectives	
(1)	(2)	(3)	
501 to 1 000	13	0	
1 001 to 3 000	20	1	
3 001 to 10 000	32		
10 001 to 35 000	50	3	
35 001 and above	80	5	

A-3 CRITERION FOR CONFORMITY

A-3.1 All the fittings selected in the sample shall be visually examined and inspected for dimensions and tolerances. A fitting in one or more requirements shall be considered as defective.

A-3.2 A lot shall be considered as having conforming to the requirements of this standard if the number of defective fittings as obtained in A-3.1 does not exceed the corresponding permissible number of defectives in col 3 of Table 2.

Standard Mark The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted

to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. CED 33 (4832)

Amendments Issued Since Publication			
Amend No.	Date of Issue	Text Affected	
	,		
F	BUREAU OF INDIAN STANDARDS		

Headquarters:

Manak	Bhavan,	9 Bahadur	Shah Zafar	Marg, New	Delhi 110002

Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha (Common to all Offices)

Regional Offices:

Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	$ \begin{cases} 331 & 01 & 31 \\ 331 & 13 & 75 \end{cases} $
Rastern : 1/14 C. I.T. Scheme VII M. V. I.P. Road. Maniktola	37 86 62

Eastern: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola 37 86 62 CALCUTTA 700054

Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036 2 18 43

Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113 41 29 16

Western: Manakalaya, E9 MIDC, Marol, Andheri (East) 6 32 92 95 BOMBAY 400093

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. PATNA. TRIVANDRUM.